



UTPT Reach Stacker & Telehandler Tires

The UTECH UTPT is designed with reinforced architecture, improved heat dissipation and wear resistance for port handling equipment that requires the tires to go through thousands of round trips over abrasive surfaces each day.



Parts Details Of UTPT Reach Stacker & Telehandler Tires

Lessen the heat build-up and offer excellent self-cleaning

- The open shoulder groove design lessens the heat build-up and offers excellent self-cleaning

Provide 10% extra load capacity and to get rid of the failures caused by frequent twisting

- The casing and bead are reinforced to provide 10% extra load capacity and to get rid of the failures caused by frequent twisting.



Ensure low heat generation and longer life-cycle

- Low heat build-up and wear resistance compound used to ensure low heat generation and longer life-cycle.

Specifications of UTPT Reach Stacker & Telehandler Tires

Size	Star Rating	TRA Code	Rim Width & Flange	Overall Width		Overall Diameter		Tread Depth		Load Index/Speed symbol	Type
				in	mm	in	mm	32nds	mm		
12.00R24	**	IND-5	8.5V/1.6	12.4	315	50.2	1275	50	40	178A5	TT/TL
14.00R24	***	IND-5	10.00W/10.0	14.76	375	53.86	1368	76	60	196A5	TT/TL
18.00R25	***	IND-4	13.00/2.5	19.61	498	65.87	1673	80	63.5	214A5	TL
Size	Star Rating	TRA Code	Rim Width & Flange	Overall Width		Overall Diameter		Tread Depth		Load Index/Speed symbol	Type
				in	mm	in	mm	32nds	mm		
12.00R24	**	IND-5	8.5V/1.6	12.4	315	50.2	1275	50	40	178A5	TT/TL
14.00R24	***	IND-5	10.00W/10.0	14.76	375	53.86	1368	76	60	196A5	TT/TL